

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	7	(rigid with sealing with (housing or casing)) and (clean\$3 with (fan or blades))	USPA T; US-P GPUB
2	BRS	L2	234	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing)	USPA T
3	BRS	L3	53	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings)	USPA T
4	BRS	L4	19	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and volt\$3	USPA T
5	BRS	L5	3	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and volt\$3	USOC R
6	BRS	L6	0	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and ("dc" or "d.c." or "direct current")	USOC R

	Type	L #	Hits	Search Text	DBs
7	BRS	L7	12	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and ("dc" or "d.c." or "direct current")	USPA T
8	BRS	L8	0	fan and (clean\$3 with blades) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and ("dc" or "d.c." or "direct current")	EPO; JPO; DERW ENT
9	BRS	L9	0	fan and (clean\$3 with fan) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and ("dc" or "d.c." or "direct current")	EPO; JPO; DERW ENT
10	BRS	L10	20	fan and (clean\$3 with fan) and seal\$3 and bearings and (housing or casing) and (seal\$3 with bearings) and ("dc" or "d.c." or "direct current")	USPA T; EPO; JPO; DERW ENT
11	BRS	L13	93	fan and (clean\$3 with blade\$1) and seal\$3 and bearing and fluid	USPA T; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
12	BRS	L14	10	fan and (clean\$3 with blade\$1) and seal\$3 and bearing and fluid and volt	USPA T; EPO; JPO; DERW ENT
13	BRS	L15	21	fan and (clean\$3 with blade\$1) and seal\$3 and bearing and liquid and volt	USPA T; EPO; JPO; DERW ENT
14	BRS	L12	148	fan and (clean\$3 with blade\$1) and seal\$3 and bearing and liquid	USPA T; EPO; JPO; DERW ENT
15	BRS	L11	301	fan and (clean\$3 with blade\$1) and seal\$3 and bearing	USPA T; EPO; JPO; DERW ENT
16	BRS	L16	150	fan and (clean\$3 with blade\$1) and seal\$3 and bearing	USOC R

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	1	liquid near3 impermeable near3 seal	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
2	BRS	L2	0	moisture near3 impermeable near3 seal	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
3	BRS	L3	0	moisture near3 impermeable near3 seal\$3	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
4	BRS	L4	9	impermeable near3 seal\$3	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
5	BRS	L5	0	seal\$3 near3 from near3 liquid	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
6	BRS	L6	0	seal\$3 near3 from near3 moisture	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
7	BRS	L7	0	seal\$3 near3 from near3 water	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
8	BRS	L8	0	seal\$4 near4 from near4 liquid	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
9	BRS	L9	10	seal\$4 near4 from	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
10	BRS	L10	75041	seal\$4 near4 liquid	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
11	BRS	L11	4739	10 and air and circulat\$3	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
12	BRS	L12	891	11 and fan	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
13	BRS	L13	140	12 and ((casing or motor) with seal\$3)	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
14	BRS	L15	13	Gray-Michael\$.xa. and fan and seal\$3	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
15	BRS	L16	31	Gray-Michael\$.xa. and fan	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
16	BRS	L17	4391	seal\$3 with motor with bearings	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
17	BRS	L18	258	seal\$3 with motor with bearings with liquid	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
18	BRS	L19	97	18 and (fan or air)	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	L #	Hits	Search Text	DBs
19	BRS	L20	2	6177744.pn.	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
20	BRS	L21	2	6177744.pn. and seal\$3	USPA T; US-P GPUB ; EPO; JPO; DERW ENT
21	BRS	L22	2	6177744.pn. and seal\$3 and (liquid or moisture or fluid)	USPA T; US-P GPUB ; EPO; JPO; DERW ENT

	Type	Hits	Search Text	DBs
52	BRS	157	(((((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with cylinder with signal\$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT
53	BRS	30	(((((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with cylinder with signal\$3 with ends)	USPAT; US-PGPUB; EPO; JPO; DERWENT
54	BRS	56	(((((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with (cylinder or piston) with signal\$3 with ends)	USPAT; US-PGPUB; EPO; JPO; DERWENT
55	BRS	0	fan with liquid with seal with impermeable	USPAT; US-PGPUB; EPO; JPO; DERWENT
56	BRS	2659	fan and (seal with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
57	BRS	29	fan and (seal with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	Hits	Search Text	DBs
58	BRS	23	fan and air and (seal with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
59	BRS	81	fan and air and (seal\$3 with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
60	BRS	904	fan and (circulat\$3 with air) and (prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
61	BRS	111	fan and (circulat\$3 with air) and (prevent\$3 with moisture with seal\$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT
62	BRS	28	(415/\$.ccls. or 417/\$.ccls.) and (air with circulat\$3) and (prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
63	BRS	99	(cool\$3 with fan) and (seal\$3 with (casing or bearing) with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
64	BRS	30	(air with circulat\$4 with fan) and (seal with prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	Hits	Search Text	DBs
52	BRS	157	(((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with cylinder with signal\$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT
53	BRS	30	(((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with cylinder with signal\$3 with ends)	USPAT; US-PGPUB; EPO; JPO; DERWENT
54	BRS	56	(((piston with (contact\$3 or colli\$5))) and (piston with sens\$3)) and (piston with sens\$3 with detect\$3)) and cylinder and (sens\$3 with (cylinder or piston) with signal\$3 with ends)	USPAT; US-PGPUB; EPO; JPO; DERWENT
55	BRS	0	fan with liquid with seal with impermeable	USPAT; US-PGPUB; EPO; JPO; DERWENT
56	BRS	2659	fan and (seal with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
57	BRS	29	fan and (seal with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	Hits	Search Text	DBs
58	BRS	23	fan and air and (seal with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
59	BRS	81	fan and air and (seal\$3 with casing with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
60	BRS	904	fan and (circulat\$3 with air) and (prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
61	BRS	111	fan and (circulat\$3 with air) and (prevent\$3 with moisture with seal\$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT
62	BRS	28	(415/\$.ccls. or 417/\$.ccls.) and (air with circulat\$3) and (prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
63	BRS	99	(cool\$3 with fan) and (seal\$3 with (casing or bearing) with (moisture or liquid))	USPAT; US-PGPUB; EPO; JPO; DERWENT
64	BRS	30	(air with circulat\$4 with fan) and (seal with prevent\$3 with moisture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
65	BRS	90	"explosion-proof motor"	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	Hits	Search Text	DBs
66	BRS	44	"explosion-proof motor" and (fan or air)	USPAT; US-PGPUB; EPO; JPO; DERWENT
67	BRS	3	("explosion-proof motor" with (liquid or moisture))and (fan or air)	USPAT; US-PGPUB; EPO; JPO; DERWENT
68	BRS	482	(sealed near3 motor) and fan	USPAT; US-PGPUB; EPO; JPO; DERWENT
69	BRS	29	(sealed near3 motor near3 air) and fan	USPAT; US-PGPUB; EPO; JPO; DERWENT
70	BRS	54	(sealed near3 motor near3 air) and (direct current or "dc" or "d.c.")	USPAT; US-PGPUB; EPO; JPO; DERWENT
71	BRS	3	"5270596"	USPAT; US-PGPUB; EPO; JPO; DERWENT
72	BRS	1	"5270596" and fan	USPAT; US-PGPUB; EPO; JPO; DERWENT
73	BRS	911	"dc motor" with fan	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	Hits	Search Text	DBs
74	BRS	31	Gray-Michael\$.xa. and fan	USPAT; US-PGPUB; EPO; JPO; DERWENT
75	BRS	2	6454539.pn.	USPAT; US-PGPUB; EPO; JPO; DERWENT
76	BRS	11	"4776761"	USPAT; US-PGPUB; EPO; JPO; DERWENT
77	BRS	8	"5245691"	USPAT; US-PGPUB; EPO; JPO; DERWENT
78	BRS	5	"5252795"	USPAT; US-PGPUB; EPO; JPO; DERWENT
79	BRS	17	"5304035"	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	67	416/\$.ccls. and (box near3 fan)	USP AT
2	BRS	L2	104 826	416/\$.ccls. or 417/\$.ccls. or 415/\$.ccls.	USP AT
3	BRS	L3	78	2 and (fan with housing) and (housing with front with rear) and motor and electric	USP AT
4	BRS	L4	33	2 and (fan with housing) and (housing with front with back) and motor and electric	USP AT
5	BRS	L5	871	2 and (fan near2 housing)	USP AT
6	BRS	L6	7	2 and (fan near2 housing) and ("12 volt" or "twelve volt")	USP AT
7	BRS	L7	72	2 and (fan near2 housing) and ("dc" or "direct current" or "d.c.")	USP AT
8	BRS	L8	303	417/423.1.ccls.	USP AT
9	BRS	L9	249 0	D\$/\$.ccls. and fan	USP AT
10	BRS	L10	32	9 and (box near2 fan)	USP AT

	Type	L #	Hits	Search Text	DBs
11	BRS	L11	123	D23/381.ccls.	USP AT
12	BRS	L12	234	D23/382.ccls.	USP AT

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	29	((fan) or (air near2 circulat\$3)) and (motor with impermeable)	USP AT; EPO ; JPO; DER WEN T
2	BRS	L2	9	fan with motor with impermeable	USP AT; EPO ; JPO; DER WEN T
3	BRS	L3	7	fan with motor with watertight	USP AT; EPO ; JPO; DER WEN T
4	BRS	L4	375	fan with motor with sealed	USP AT; EPO ; JPO; DER WEN T

	Type	L #	Hits	Search Text	DBs
5	BRS	L5	57	fan with motor with sealed with cas\$3	USP AT; EPO ; JPO; DER WEN T
6	BRS	L6	57	(fan with motor with sealed with cas\$3) and seal\$3	USP AT; EPO ; JPO; DER WEN T
7	BRS	L7	12	(fan with motor with sealed with cas\$3) and seal\$3 and (plastic or polymer\$3)	USP AT; EPO ; JPO; DER WEN T